




Холодильные установки для автотранспортных средств средней грузоподъемности

	Внешняя тем-ра 30 °С			метры		Внешняя тем-ра -29 °С		
	-20°C Ватт	0°C Ватт		0°C/6°C	-20°C	Ватт	Ватт	
TS-600	6200	9500	3200	9,0+	9,0+	4900	3900	525
TS-500	5900	8400	3200	9,0	7,5	4540	3660	520
TS-300	4000	6750	2720	7,5	6,5	4100	2850	440
TS-200	3600	6100	2720	6,5	6,0	3660	2440	435
XDS SR (R-404 A)	5900	8400	3100	9,0	7,5	4540	3660	470
URD-III MAX	5020	7640	3740	9,0	8,0	-	-	555
RD-II SR (R-404A)	5200	6800	3060	9,0	7,5	4400	3000	470
RD-II SR (R-134A)	3100	7600	3060	9,0	7,5	4250	2850	470
KD-II SR (R-404A)	4000	6400	2720	7,5	7,5	4100	2850	372
KD-II SR (R-134A)	2330	5570	2720	7,5	6,5	3960	2700	372
MD-II SR (R-404A)	3350	5200	2720	6,5	6,5	3660	2440	368
MD-II SR (R-134A)	1945	4665	2720	6,0	6,0	3520	2300	368
UMD-II MAX	3590	5670	2040	6,5	6,0	-	-	375
SDZ MAX	2500	4000	1700	6,5	5,5	2500	2100	345
SDZ	1535	3700	1700	6,5	4,0	2500	2100	345
CD MAX	2500	3400	1800	6,0	5,5	2290*	2290*	311
CD	1500	3400	1800	6,0	4,0	2290*	2290*	311